

() .

.

2160

/ 1080

540

22 26

(24) ,

(

).

I

60950-1-2009, IEC 60950-1-2014

51841-2001.

51841-2001

61131-2-92.

81406-21 30

2026 .

020/2011 07.05.2023 .

L BS-15-

- - 15
- USB2.0 – 2
- 10/100/1000 Gigabit Ethernet – 2
- – 8
- (): Intel Atom, 4 1,9
- : 8 DDR - 4 - 2400
- : 16 e C + 60 SSD
- : Intel® Gen 9 HD Graphics
2560x1600 60
- Display port
- : (),
- « - »



16- ID-16k24

- , 24 ,
- :
- , ;
- («+» «-») 4
- ;
- «0» – 0 8 ;
- «1» – 18 30 ;
- «1» – 24 ;
- –5 ;
- –
- 5 ;
- 1500
- RS-485 1200



16- OD-16k24

24 ,

- ,
- -1 , ;
- - +18 +30 ;
- - 1 ();
- - ;
- - ;
- (1)- 0,1 ;
- «0» 30 -
- 8 ;
- :
- ISO - 10 ;
- RS-485 38400 / -15 ;
- RS-485 9600 / -40 .
- - , 200 ;
- - , 200 ;
- RS-485 1200



8- IA-8k42

- 4 20 26.011-80;
- — 0,1 %;
- – 120 ;
- 15 ;
- – ± 24 ;
- – 24 ;
- () – ;
- 1500 ;
- – 100
- RS-485 1200



4- OA-4k42-M

:

- 4 20 26.011-80;
- - 0,1 %;
- - 700 ;
- -⁶10
- -
- 60 ;
- -
- 1500 ;
- - 100
- ;
- RS-485 1200



3- IF-3k

()

12-16000 ,

:

- -3.
- - ;
- - 12 16000 ;
- 0,2 12
- 0,1%.
- - 3 .
- - 2,
- - , 2
- 30 , 120 .



D-1k/I-01

-1k/CD

:

•

()

-

-

•

-2

•

-2

•

-

:

•

-

-

(),

•

-2;

•

-24 ;

•

, -0,3 ;

•

-(50±1) ;

•

- 5 95%;

•

-

•

- 20 .



4- USB/RS-485-4k

L BS-15-

RS-485.

:

- RS-485 – 4
- - 2400 256000 /
- 38400 / - 1200
- - « » 5



COM/RS-485

RS-485.

:

-
- ;
-

24

RS-485

4- USB/RS-485-4k

